


# AMC-1H



# AMBIENT-SENSING THERMOSTAT FOR HAZARDOUS LOCATIONS







#### **PRODUCT OVERVIEW**

The nVent RAYCHEM AMC-1H ambient-sensing thermostat is designed to control heat-tracing systems used for freeze protection in hazardous locations. The thermostat responds to ambient temperature changes and has an adjustable set point. The AMC-1H can be used to control a single heat-tracing circuit or as a pilot control of a contactor switching multiple heat-tracing circuits.

## **SPECIFICATIONS**

Enclosure TYPE 4, 7, 9 lacquer-coated cast-

aluminum housing, stainless steel

hardware

Entries One 3/4-in (19 mm) NPT conduit hub

Set point range 15°F to 140°F (-9°C to 60°C) Sensor exposure -40°F to 160°F (-40°C to 71°C)

limits

Housing exposure  $-40^{\circ}\text{F}$  to  $140^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $60^{\circ}\text{C}$ )

limits
Switch SPDT

Electrical rating 22 A at 125 / 250 / 480 Vac

Accuracy  $\pm 6^{\circ}F (\pm 3.3^{\circ}C)$ 

Deadband 2°F to 12°F (1.1°C to 6.7°C) above

±3°F (±1.7°C)

actuation temperature

Setpoint

repeatability

Sensor type Fixed fluid-filled (silicone) bulb and

capillary

Sensor material 300 series stainless steel
Connection Screw terminals, 10–14 AWG

terminals (2-5 mm<sup>2</sup>)

# **APPROVALS**

#### Hazardous Locations







Class I, Div. 1 and 2, Groups B, C, D Class II, Div. 1 and 2, Groups E, F, G Class III

Raychem-DS-H55202-AMC1H-EN-1805 nVent.com | 1

## **North America**

Tel +1.800.545.6258 Fax +1.800.527.5703 thermal.info@nvent.com

# **Europe, Middle East, Africa**

Tel +32.16.213.511 Fax +32.16.213.604 thermal.info@nvent.com

# **Asia Pacific**

Tel +86.21.2412.1688 Fax +86.21.5426.3167 cn.thermal.info@nvent.com

# **Latin America**

Tel +1.713.868.4800 Fax +1.713.868.2333 thermal.info@nvent.com



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

em-DS-H55202-AMC1H-EN-1805