

CERTIFICATE OF COMPLIANCE

Certificate Number E94389
Report Reference E94389-19841005
Issue Date 2021-MARCH-01

Issued to: ERICO INTERNATIONAL CORPORATION
34600 SOLON RD
SOLON OH 44139-2631

**This certificate confirms that
representative samples of**

LUMINAIRE FITTINGS
Suspended ceiling fixture clips Cat. No. 2G9, 2G9S10,
4G16, 4G16G, 4G16H, 4G161.5, 4G162, 4G163, 4G8,
4G8WH, 4G8S7, 4G8S7WH, 4G9, 515, 515A, IDS, IDS1.5,
IDS2, IDS9, IDS9.5

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

UL 1598, Luminaires
See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190307-E94389
Report Reference E94389-20040524
Issue Date 2019-MARCH-07

Issued to: ERICO INTERNATIONAL CORPORATION
34600 SOLON RD
SOLON OH 44139-2631

**This certificate confirms that
representative samples of**

LUMINAIRE FITTINGS
See addendum page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

UL 1598 & CSA C22.2 No. 250.0-08, Luminaires
See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190307-E94389
Report Reference E94389-20040524
Issue Date 2019-MARCH-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models/Product:


USL, CNL Luminaire fittings, Luminaire cable supports, Cat. Nos. SLfwLz, SLfwLzT, SLfwYx, SLfwYHx, where: f = D or K locking device; w = 1.5 mm or 2 mm; z = 0.5 m thru 50 m; x = 100 mm thru 3000 mm;
SLfwQTx, SLfwYxLz, SLfwYHxLz, f = D or K locking device; w = 1.5 mm or, 2 mm; z = 0.5 m thru 50 m; x = 100 mm thru 3000 mm;
SLDwLzS, w = 1.5 mm; z = 0.5 m thru 50 m; x = 100 mm thru 3000 mm;
SLfwYxLzHp, where: f = D or K locking device; w = 1.5 mm or, 2 mm; x = 100 mm thru 999 mm or 1MO to 3 MO (1 meter increment with 10 cm increments); z = 050 (50 mm), or 1 to 50 (1 meter increments); p = no suffix is steel, or "S" is stainless steel (for 1.5 mm cable only).

SLfwLzm, where f = D or K locking device; w = 15 or 2 where 15 = 1.5mm or 2 = 2mm; z = 050 (50mm), or 1 to 50 (1 meter increments); m = 4H24, 4H58, AB, LP, SF, DH, SEM6, SEM8, SEM10, SE250, E, SLK2C50, SLK2C200

Cat. Nos. SLDwLz, SLDwLzT, SLDwYx, SLDwYHx, where: w = 3 mm; z = 0.5 m thru 50 m; x = 100 mm thru 3000 mm; SLDwQTx, SLDwYxLz, SLDwYHxLz, w = 3 mm; z = 0.5 m thru 50 m; x = 100 mm thru 3000 mm;

SLDwYxLzHp, where: w = 3 mm; x = 100 mm thru 999 mm or 1MO to 3 MO (1 meter increment with 10 cm increments); z = 050 (50 mm), or 1 to 50 (1 meter increments); p = no suffix is steel, or "S" is stainless steel (for 1.5 mm cable only).

All may be followed by BP or TP or Rxx, where xx is up to a two-digit integer.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

